

Description

PRONTO (SP) 80W90 6/1QT

| Inspection Information | Test Method | Typical Value |
|-----------------------------------|--------------------|----------------------|
| Gravity, °API | ASTM D287 | 28.53 |
| Specific Gravity at 60°F (15.6°C) | ASTM D4052 | 0.8842 |
| Flash Point, °C | ASTM D92 | 232 |
| Flash Point, °F | ASTM D92 | 450 |
| Viscosity at 40°C, cSt | ASTM D445 | 140.8 |
| Viscosity at 100°C, cSt | ASTM D445 | 14.01 |
| Viscosity Index | ASTM D2270 | 96 |
| Pour Point, °C (°F) | ASTM D5950 | -33°C (-27°F) |
| Brookfield Viscosity at -26°C, cP | ASTM D2983 | 100,000 |
| Color | ASTM D1500 | 3 |
| Phosphorus, wt. % | ASTM D5185 | 0.047 |
| Sulfur, wt. % | ASTM D4951 | 1.6 |

Claims Information

| | |
|---------------------------|--------------------|
| API GL-5 | Meets Requirements |
| Ford M2C108C | Meets Requirements |
| Limited Slip | Suitable for Use |
| Mack GO-J, GO-H, GO-G | Meets Requirements |
| MAN 342 M-1 | Meets Requirements |
| MAN 342 M-2 | Meets Requirements |
| Meritor 0-76D | Meets Requirements |
| MT-1 | Meets Requirements |
| SAE J2360, MIL-2105E/F | Meets Requirements |
| Scania STO 1.0 | Meets Requirements |
| ZF TE ML-07A, ZF TE ML-08 | Meets Requirements |