

Description

PRONTO (SP) UNIV TRAC FLD 5GL

| Inspection Information | Test Method | Typical Value |
|-----------------------------------|--------------------|----------------------|
| Gravity, °API | ASTM D287 | 30.57 |
| Specific Gravity at 60°F (15.6°C) | ASTM D4052 | 0.8731 |
| Flash Point, °C | ASTM D92 | 224 |
| Flash Point, °F | ASTM D92 | 435 |
| Viscosity at 40°C, cSt | ASTM D445 | 67.8 |
| Viscosity at 100°C, cSt | ASTM D445 | 9.613 |
| Viscosity Index | ASTM D2270 | 122 |
| Pour Point, °C (°F) | ASTM D5950 | -39°C (-38°F) |
| Brookfield Viscosity at -35°C, cP | ASTM D2983 | 48,000 |
| Color | ASTM D1500 | 2.5 |
| Zinc, wt. % | ASTM D5185 | 0.139 |
| Phosphorus, wt. % | ASTM D5185 | 0.13 |
| Calcium, wt. % | ASTM D5185 | 0.334 |

Claims Information

| | |
|---|------------------|
| AGCO 821XL, 25741, 25743, 246634, 272843 | Suitable for Use |
| Allison C-4, C-3, C-2 | Suitable for Use |
| API GL-4 | Suitable for Use |
| Case JIC 144, 145 | Suitable for Use |
| Case MS-1317, 1230, 1216, 1209, 1210 (MAT 3506), 1207, 1206, 1205, 1204, 143, 144, 145, 185, Case-O-Matic Type A | Suitable for Use |
| CAT TO-2 | Suitable for Use |
| Clark Lift Truck Transmission Fluid TA 12, TA 18, HR 500, HR 600 | Suitable for Use |
| CNH (MAT 3526, 3525, 3506, 3505) | Suitable for Use |
| Deere J20C/J20A | Suitable for Use |
| Denison HF-0, HF-1, HF-2 | Suitable for Use |
| Deutz, Allis-Chalmers Power Fluid 821 | Suitable for Use |
| Ford ESN-M2C143A-d (NH-410B), ESN-M2C86A, B, C, ESN-M2C-41, 41A & B, 43, ESN-M2C-48B & C, ESN-M2C53A & B, ESN-M2C-77A, 78A, 79A, ESN-M2C-142A, ESN-M2C-143, ESN-M2C-92A, ESN-M2C-159A-C | Suitable for Use |
| Ford FNHA-2-C-200, Ford FNHA-2-C-201, Ford M2CA-C | Suitable for Use |
| Ford New Holland M2C41A,B, M2C48B, M2C53A, M2C86A, M4864A & B | Suitable for Use |
| Ford New Holland M2C86B, M2C134A, B, C, D (NH-410B) | Suitable for Use |
| Hesston-Fiat AF-87, Oilofiat Tutela Multi-F | Suitable for Use |
| International Harvester Hy-Tran B-6 | Suitable for Use |
| John Deere J14A-C, 303 | Suitable for Use |
| Komatsu AXO80 and prior | Suitable for Use |
| Kubota UDT, Kioti, Komatsu KES 07.866, AXO80, Komatsu-Dresser B06.0002, Dresser, Industry of Machinery and Tractors, JCMAS HK P-041 & P-042 | Suitable for Use |
| Massey Ferguson M-1103A, M-1103B, M-1110, M-1127, M-1127A, M-1127B | Suitable for Use |
| Massey Ferguson M-1129, M-1129A, M-1135, M-1138, M-1141, M-1143, M-1145 | Suitable for Use |
| Massey Ferguson M-1135, M-1141, M-1143, M-1145 | Suitable for Use |
| MAT 3540 | Suitable for Use |
| MAT 3540, 3525, 3526, 3510, 3505 | Suitable for Use |
| MS-1230 (Poclairn Equipment) Hydraulic Fluid for High Pressure Systems | Suitable for Use |
| Oliver/White/Minn.-Moline/New Idea 55, New Idea 5J, Q-1826, Q1766, Q1722, Q1766B, Q1705, Q1802, Type 55, 23M, 24M | Suitable for Use |
| Sauer/Danfoss (Sundstrand) Hydrostatic Transmission Fluid, Quatrol, Renk-Doromat 87.3, 874A, 874B | Suitable for Use |
| Sperry Vickers M-2950-S Mobil Hydraulics, I-286-S Industrial Hydraulics | Suitable for Use |
| Steiger Hyd-Trans SEMS 17001 | Suitable for Use |
| Valmet, Valtractores, Versatile Gear and HydrTrans Fluid, Yanmar, New Idea Power Units, Leyland, Belarus & Fiat | Suitable for Use |
| Versatile ESN-M2C134D (FNHA-2-C-201.00) | Suitable for Use |
| Versatile Gear and Hyd-Trans | Suitable for Use |
| Vickers 35VQ25 | Suitable for Use |

Claims Information

| | |
|--|------------------|
| Vickers/Eaton I-286-S, M-2950-S | Suitable for Use |
| Volvo WB101, Volvo VCE 1273.03 | Suitable for Use |
| ZF TE-ML-03E Torque Converter Transmission | Suitable for Use |
| ZF TE-ML-05F Off-Road Axles, exception of hypoid gears | Suitable for Use |