

Description

PRONTO (SP)ATF DEX/MERC 12/1QT

Inspection Information	Test Method	Typical Value
Gravity, °API	ASTM D287	33.42
Specific Gravity at 60°F (15.6°C)	ASTM D4052	0.858
Flash Point, °C	ASTM D92	204
Flash Point, °F	ASTM D92	400
Viscosity at 40°C, cSt	ASTM D445	34.99
Viscosity at 100°C, cSt	ASTM D445	7.139
Viscosity Index	ASTM D2270	179
Pour Point, °C (°F)	ASTM D5950	-51°C (-60°F)
Brookfield Viscosity at -40°C, cP	ASTM D2983	12,537
Color	ASTM D1500	Red
Copper Strip Corrosion (3 hrs at 100°C)	ASTM D130	1B
Rust Protection	ASTM D665A	Pass
Hydrolytic Stability Test	ASTM D2619	Pass
Foam Test	ASTM D892	<100/0 ml

Claims Information

Allison C-4	Meets Requirements
Allison C-4, C-3, C-2	Suitable For Use
CAT TO-2	Suitable for Use
Dexron III G/H, Dexron II D/E, Dexron, AW1	Meets Requirements
Ford Mercon, Ford ESP-M2C166-H	Meets Requirements
MB 236.1, Allison V-730D	Suitable for Use
Type A	Suitable for Use