



THE SMART CHOICE FOR AUTO PARTS



ANTIFREEZE-COOLANT



Pronto
Antifreeze-Coolant
1 U.S. GAL. (3.78 L)
Part # 010PR



Pronto
Antifreeze-Coolant (50/50)
1 U.S. GAL. (3.78 L)
Part # 150PR

Pronto Antifreeze-Coolant is a conventional (green), ethylene glycol based antifreeze for use in automotive and light duty diesel applications. **Pronto Antifreeze-Coolant** contains inhibitors that provide maximum protection from freezing to -84°F and boil-over to +276°F. Its formula protects all metals, including aluminum, against damaging rust and corrosion when used as recommended.

FEATURES & BENEFITS

- Provides superior corrosion protection for all metals including aluminum
- Meets heavy duty standards for low silicate antifreeze
- One product for automobiles, diesel engines, and heavy duty equipment
- Maximum Freeze-Up Protection to -84°F Boil-Over Protection to +276°F
- Provides Year-Round Protection
- Protects Against Damaging Rust and Corrosion
- Compatible with All Conventional Green Antifreeze
- When used in heavy-duty applications, the addition of a separate Supplemental Coolant Additive (SCA) is recommended at initial fill and when topping off. See owner's manual for engine manufacturer's requirements.

SPECIFICATIONS

Meets the performance requirements and specifications for aftermarket antifreeze/coolants including:

Heavy Duty

- ASTM D-4985
- Cummins 90T8-4
- Caterpillar
- TMC RP302-B
- John Deere H24B1/C1
- Mack Truck
- Volvo-GM Heavy Truck

Automobile

- ASTM D-3306
- ASTM D-4340
- Ford ESE-M97B44-A
- Chrysler MS7170

CHEMICAL PROPERTIES

CHART BELOW PERTAINS TO CONCENTRATED PRODUCT ONLY.

Properties

Specific Gravity at 60/60°F
Boiling Point, Reflux
Foam Test
pH, 50% Volume Solution
Reserve Alkalinity
Flash Point, COC
Total Water, Wt. %
Total Glycols, Wt. %

Typical Values

1.120-1.130
325°F Min.*
50 ml./3 sec. Max.
10.5 Min. - 11.0 Max.
11 ml. Min.
250°F Min.
5% Max.
95% Min.

ASTM Test Method

D 1122
D 1120
D 1881
D 1287
D 1121
D 92
D 1123
E 202

Part # 010PR

Pack	6/1 Gallon (3.78 L)
Item No.	P084AF6P
Each UPC	0-71621-63186-7
Case UPC	0-71621-63187-4
Case SCC	1-00-71621-63186-4
Pack Dimensions	L 16" x W 12.5" x H 12.25"
Pack Cubes (Ft. ³)	1.53
Pack Weight (lbs.)	60.0 Lbs
Pallet Weight (lbs.)	2210.0 Lbs
Pallet Stack	36 Cases (4 Layers of 9)

Part # 150PR

Pack	6/1 Gallon (3.78 L)
Item No.	P081AF6P
Each UPC	0-71621-63188-1
Case UPC	0-71621-63189-8
Case SCC	1-00-71621-63188-8
Pack Dimensions	L 15.5" x W 12.5" x H 12.25"
Pack Cubes (Ft. ³)	1.53
Pack Weight (lbs.)	60.0 Lbs
Pallet Weight (lbs.)	2210.0 Lbs
Pallet Stack	36 Cases (4 Layers of 9)

FULL STRENGTH ANTIFREEZE

ANTIFREEZE/ BOIL PROTECTION CHART °F	% of Antifreeze in Cooling System	PROTECTS FROM	
		Freezing Down to	Boiling Up to*
50		-34°F	265°F
60		-62°F	270°F
70		-84°F	276°F

*Using a 15 lb. pressure cap at sea level