

# pronto®

THE SMART CHOICE FOR AUTO PARTS

**TECH  
SELECT**



## FOR ALL VEHICLES ANTIFREEZE-COOLANT



Pronto  
FOR ALL VEHICLES  
Antifreeze-Coolant  
1 U.S. GAL. (3.78 L)  
Part # 076PR



Pronto  
FOR ALL VEHICLES  
Antifreeze-Coolant (50/50)  
1 U.S. GAL. (3.78 L)  
Part # 077PR

**PRONTO FOR ALL VEHICLES Antifreeze-Coolant** provides protection to 150,000 miles or 5 years. Simply follow the directions to convert your car's cooling system to a new level of protection & convenience!  
**PRONTO FOR ALL VEHICLES Antifreeze-Coolant** protects all cooling system metals against corrosion, and is silicate-free and phosphate-free. Meets or exceeds automotive performance requirements of many specifications.

### FEATURES & BENEFITS

- Provides maximum protection for 5 years or 150,000 miles when a complete cooling system flush and fill is performed
- Silicate-free; Phosphate-free
- Safe for use in all engine metals, including aluminum
- Maximum Freeze-Up Protection to -84°F Boil-Over Protection to +276°F
- Compatible for use in all automobiles and light duty trucks
- Meets ASTM D-3306 and ASTM D-4340 and features a coolant technology that is compatible for use in all automobiles and light trucks, regardless of make, model, year or original antifreeze color.
- Compatible for use in Dex-Cool applications and Ford G-05

### CHEMICAL PROPERTIES

#### Properties

Specific Gravity at 60/60°F  
Boiling Point, Reflux  
Foam Test  
pH, 50% Volume Solution  
Flash Point, COC  
Total Water, Wt. %  
Total Glycols, Wt. %  
ColorYellow

CHART BELOW PERTAINS TO CONCENTRATED PRODUCT ONLY.

#### Typical Values

1.115-1.124  
325°F Min.\*  
50 ml./3 sec. Max.  
7.5 Min. - 10.0 Max.  
250°F Min.  
5% Max.  
95% Min.

#### ASTM Test Method

D 1122  
D 1120  
D 1881  
D 1287  
D 92  
D 1123  
E 202

**This is strictly a guide.**

*Please consult your owner's manual for specified antifreeze usage.*

Color bars at right approximate antifreeze fluid colors.

|   | Pronto Antifreeze-Coolant | Pronto Antifreeze-Coolant (50/50) | Pronto FOR ALL VEHICLES Antifreeze-Coolant | Pronto FOR ALL VEHICLES Antifreeze-Coolant (50/50) |
|---|---------------------------|-----------------------------------|--|--|
| General Motors (1994-Older)                       | x                         | x                                 | x  | x  |
| General Motors (1995-Newer)                       |                           |                                   | x  | x  |
| Saturn (All)                                      |                           |                                   | x  | x  |
| Chrysler (2001-Older)                             | x                         | x                                 | x  | x  |
| Chrysler (2001-Newer)                             |                           |                                   | x  | x  |
| Ford (2001-Older)                                 | x                         | x                                 | x  | x  |
| Ford (2002-Newer Trucks & 2003-Newer Automobiles) |                           |                                   | x  | x  |
| Asian (All)                                       |                           |                                   | x  | x  |
| European (All)                                    |                           |                                   | x  | x  |
| Heavy-Duty Diesel (All)                           | x*                        | x*                                |  |  |

\* With addition of SCA Additive

| Part # 076PR                   |                            |
|--------------------------------|----------------------------|
| Pack                           | 6/1 Gallon (3.78 L)        |
| Item No.                       | P082AF6P                   |
| Each UPC                       | 0-71621-63190-4            |
| Case UPC                       | 0-71621-63191-1            |
| Case SCC                       | 1-00-71621-63190-1         |
| Pack Dimensions                | L 16" x W 12.5" x H 12.25" |
| Pack Cubes (Ft. <sup>3</sup> ) | 1.53                       |
| Pack Weight (lbs.)             | 60.0 Lbs                   |
| Pallet Weight (lbs.)           | 2210.0 Lbs                 |
| Pallet Stack                   | 36 Cases (4 Layers of 9)   |

| Part # 077PR                   |                              |
|--------------------------------|------------------------------|
| Pack                           | 6/1 Gallon (3.78 L)          |
| Item No.                       | P083AF6P                     |
| Each UPC                       | 0-71621-63192-8              |
| Case UPC                       | 0-71621-63193-5              |
| Case SCC                       | 1-00-71621-63192-5           |
| Pack Dimensions                | L 15.5" x W 12.5" x H 12.25" |
| Pack Cubes (Ft. <sup>3</sup> ) | 1.53                         |
| Pack Weight (lbs.)             | 60.0 Lbs                     |
| Pallet Weight (lbs.)           | 2210.0 Lbs                   |
| Pallet Stack                   | 36 Cases (4 Layers of 9)     |

### FULL STRENGTH ANTIFREEZE

| ANTIFREEZE/<br>BOIL<br>PROTECTION<br>CHART °F | % of Antifreeze in<br>Cooling System | PROTECTS FROM    |                |
|---|--------------------------------------|------------------|----------------|
|   |                                      | Freezing Down to | Boiling Up to* |
| 50  |                                      | -34°F            | 265°F          |
| 60  |                                      | -62°F            | 270°F          |
| 70  |                                      | -84°F            | 276°F          |

\*Using a 15 lb. pressure cap at sea level

Distributed by National Pronto Association | Grapevine, TX 76051 | MADE IN THE USA