

**Description**

PRONTO MV ATF 6/1QT - US

<b>Inspection Information</b>	<b>Test Method</b>	<b>Typical Value</b>
Gravity, °API	ASTM D287	33.02
Specific Gravity at 60°F (15.6°C)	ASTM D4052	0.8601
Viscosity at 40°C, cSt	ASTM D445	35.43
Viscosity at 100°C, cSt	ASTM D445	7.56
Viscosity Index	ASTM D2270	189
Pour Point, °C (°F)	ASTM D5950	-51°C (-60°F)
Brookfield Viscosity at -40°C, cP	ASTM D2983	11,300
Color	ASTM D1500	Red

## Claims Information

Allison C-4	Suitable for Use
Audi G 052 025, 052 162, 055 025	Suitable for Use
BMW 7045E, LA2634, LT71141	Suitable for Use
BMW P/N 83 22 0 024 359, ETL-8072B	Suitable for Use
BMW P/N 83 22 0 0246 922, ETL-7045E	Suitable for Use
BMW P/N 83 22 0 403 249, ETL-8072B	Suitable for Use
BMW P/N 83 22 9 407 765, LA 2634	Suitable for Use
BMW P/N 83 22 9 407 807, LT 711 41	Suitable for Use
Chrysler 05127382AA, 68043742AA, 68157995AA, 68157995AB, 68171866AA	Suitable for Use
Chrysler AS68RC, Diamond SP-III	Suitable for Use
Dexron III G/H, Dexron II D/E, Dexron, AW1	Suitable for Use
Esso LT 71141	Suitable for Use
Ford Mercon V (XT-5-QM,XT-5-DM)	Approvable by Brand
Ford Mercon, Ford ESP-M2C166-H	Suitable for Use
Ford P/N XT-2-DX (MERC), Ford P/N XT-2-SM (SYN MERC)	Suitable for Use
Ford XT8QAW	Suitable for Use
Fuchs 3353	Suitable for Use
Honda ATF Ultra II, DW-1, Z-1, 3.0, 3.1	Suitable for Use
Hyundai NWS 9638	Suitable for Use
Hyundai/Kia/Mitsubishi Diamond ATF-MA1, ATF PA, AW, J2, J3, SK, SP-II, SP-III, RED-1, SP-IV (00232-1904/04500-00115), SP-IV M (SP4-M), SPH-IV, SP-IV-RR, JWS 3314,	Suitable for Use
IDEMITSU APOROIL ATF HP, Idemitsu K17 3100 PL085	Suitable for Use
ISUZU 08200-9001 / Genuine ATF	Suitable for Use
Jaguar P/N WSS-M2C922-A-1	Suitable for Use
JWS 3309, Any 3309	Suitable for Use
JWS 3324	Suitable for Use
MAN 339 Type Z1, Z2, V1	Meets Requirements
Mazda ATF M-III, MV, T-IV	Suitable for Use
MB236.1,2,5,6,7,9, 10, 11	Suitable for Use
MINI P/N 83 22 0 402 413	Suitable for Use
Nissan Matic-D, J, K, 402	Suitable for Use
SAAB P/N 22 717 466, 93 165 147 (AW-1)	Suitable for Use
Saturn T-IV, GM TASA, T-IV ATF, GM WS ATF, Saturn VI, 21005966, 1940700, 1940767, 22717466,88900925, 93160393,	Suitable for Use
Shell 3403 M115	Suitable for Use
Shell 3403, LA2634, Texaco 7045-E, ETL-8072B	Suitable for Use
Subaru ATF, ATF-HP	Suitable for Use
Suzuki 3314, 3317	Suitable for Use
Texaco N402	Suitable for Use

## Claims Information

Toyota T-II, T-III, T-IV, WS	Suitable for Use
Type A	Suitable for Use
Voith 55.6335 (G607)	Suitable for Use
Volvo P/N 1161540-8	Suitable for Use
Volvo Passenger Car (4 / 6 sp), Volvo 97340, 97341, 97342	Suitable for Use
VW G 052 162, 052 162 A1 A2 A6, 099, 055 025 A2	Suitable for Use
VW P/N GUS 000 162	Suitable for Use
Warren Distribution Recommends this product as suitable for use in applications specifying Allison TES-389	Suitable for Use
ZF TE-ML 03D, 04D, 05L, 09, 11B, 14A, 16L, 17C	Suitable for Use
ZF TE-ML 14B	Meets Requirements