

pronto®

THE SMART CHOICE FOR AUTO PARTS

**TECH
SELECT**



FOR ALL VEHICLES ANTIFREEZE-COOLANT



Pronto
FOR ALL VEHICLES
Antifreeze-Coolant
1 U.S. GAL. (3.78 L)
Part # 076PR



Pronto
FOR ALL VEHICLES
Antifreeze-Coolant (50/50)
1 U.S. GAL. (3.78 L)
Part # 077PR

PRONTO FOR ALL VEHICLES Antifreeze-Coolant provides protection to 150,000 miles or 5 years. Simply follow the directions to convert your car's cooling system to a new level of protection & convenience!
PRONTO FOR ALL VEHICLES Antifreeze-Coolant protects all cooling system metals against corrosion, and is silicate-free and phosphate-free. Meets or exceeds automotive performance requirements of many specifications.

FEATURES & BENEFITS

- Provides maximum protection for 5 years or 150,000 miles when a complete cooling system flush and fill is performed
- Silicate-free; Phosphate-free
- Safe for use in all engine metals, including aluminum
- Maximum Freeze-Up Protection to -84°F Boil-Over Protection to +276°F
- Compatible for use in all automobiles and light duty trucks
- Meets ASTM D-3306 and ASTM D-4340 and features a coolant technology that is compatible for use in all automobiles and light trucks, regardless of make, model, year or original antifreeze color.
- Compatible for use in Dex-Cool applications and Ford G-05

CHEMICAL PROPERTIES

Properties

Specific Gravity at 60/60°F
Boiling Point, Reflux
Foam Test
pH, 50% Volume Solution
Flash Point, COC
Total Water, Wt. %
Total Glycols, Wt. %
ColorYellow

CHART BELOW PERTAINS TO CONCENTRATED PRODUCT ONLY.

Typical Values

1.115-1.124
325°F Min.*
50 ml./3 sec. Max.
7.5 Min. - 10.0 Max.
250°F Min.
5% Max.
95% Min.

ASTM Test Method

D 1122
D 1120
D 1881
D 1287
D 92
D 1123
E 202

This is strictly a guide.

Please consult your owner's manual for specified antifreeze usage.

Color bars at right approximate antifreeze fluid colors.

	Pronto Antifreeze-Coolant	Pronto Antifreeze-Coolant (50/50)	Pronto FOR ALL VEHICLES Antifreeze-Coolant	Pronto FOR ALL VEHICLES Antifreeze-Coolant (50/50)
General Motors (1994-Older)	x	x	x	x
General Motors (1995-Newer)			x	x
Saturn (All)			x	x
Chrysler (2001-Older)	x	x	x	x
Chrysler (2001-Newer)			x	x
Ford (2001-Older)	x	x	x	x
Ford (2002-Newer Trucks & 2003-Newer Automobiles)			x	x
Asian (All)			x	x
European (All)			x	x
Heavy-Duty Diesel (All)	x*	x*		

* With addition of SCA Additive

Part # 076PR	
Pack	6/1 Gallon (3.78 L)
Item No.	P082AF6P
Each UPC	0-71621-63190-4
Case UPC	0-71621-63191-1
Case SCC	1-00-71621-63190-1
Pack Dimensions	L 16" x W 12.5" x H 12.25"
Pack Cubes (Ft. ³)	1.53
Pack Weight (lbs.)	60.0 Lbs
Pallet Weight (lbs.)	2210.0 Lbs
Pallet Stack	36 Cases (4 Layers of 9)

Part # 077PR	
Pack	6/1 Gallon (3.78 L)
Item No.	P083AF6P
Each UPC	0-71621-63192-8
Case UPC	0-71621-63193-5
Case SCC	1-00-71621-63192-5
Pack Dimensions	L 15.5" x W 12.5" x H 12.25"
Pack Cubes (Ft. ³)	1.53
Pack Weight (lbs.)	60.0 Lbs
Pallet Weight (lbs.)	2210.0 Lbs
Pallet Stack	36 Cases (4 Layers of 9)

FULL STRENGTH ANTIFREEZE

ANTIFREEZE/ BOIL PROTECTION CHART °F	% of Antifreeze in Cooling System	PROTECTS FROM	
		Freezing Down to	Boiling Up to*
50		-34°F	265°F
60		-62°F	270°F
70		-84°F	276°F

*Using a 15 lb. pressure cap at sea level

Distributed by National Pronto Association | Grapevine, TX 76051 | MADE IN THE USA