

Description

PRONTO (SP) 5W30 DXS 3/5QT

Inspection Information	Test Method	Typical Value
Gravity, °API	ASTM D287	34.93
Specific Gravity at 60°F (15.6°C)	ASTM D4052	0.8502
Flash Point, °C	ASTM D92	227
Flash Point, °F	ASTM D92	441
Viscosity at 40°C, cSt	ASTM D445	62.09
Viscosity at 100°C, cSt	ASTM D445	10.91
Viscosity Index	ASTM D2270	169
Pour Point, °C (°F)	ASTM D5950	-45°C (-49°F)
Cold Cranking Simulator at (°C), cP	ASTM D5293	4400 (-30)
High Temperature / High Shear Vis at 100°C, cP	ASTM D6616	6.9
High Temperature / High Shear Vis at 150°C, cP	ASTM D5481	3.2
Noack Volatility, % loss	ASTM D5800	12
Color	ASTM D1500	3
Zinc, wt. %	ASTM D5185	0.085
Phosphorus, wt. %	ASTM D5185	0.076
Calcium, wt. %	ASTM D5185	0.135
Sulfur, wt. %	ASTM D4951	0.3
Magnesium, wt. %	ASTM D5185	0.059
Boron, wt. %	ASTM D5185	0.023
Molybdenum, wt. %	ASTM D5185	0.0079
Sulfated Ash, wt. %	ASTM D874	0.9
Nitrogen, wt. %	ASTM D4629	0.104
Pumping Viscosity at (°C), cP	ASTM D4684	15,000 (-35)
Shear Stability, Final Viscosity in cSt	ASTM D6278	9.4
Foam Seq. I (Tendency/Stability), mL	ASTM D892 (Opt. A)	0/0
Foam Seq. II (Tendency/Stability), mL	ASTM D892 (Opt. A)	10/0
Foam Seq. III (Tendency/Stability), mL	ASTM D892 (Opt. A)	0/0
High Temperature Foaming, static foam	ASTM D6082 (Opt A)	15/0
TBN, mgKOH/g	ASTM D2896	7.9

Claims Information

API SJ, SH, SG, SF, SE, SD, SC	Meets Requirements
API SL	Meets Requirements
API SM	Meets Requirements
API SN	Meets Requirements
API SN PLUS	Meets Requirements
API SP	Approved
Chrysler MS-6395	Meets Requirements
dexos1 gen 2	Approvable by Brand
Ford WSS M2C946-B1, M2C946-A M2C929-A	Meets Requirements
Ford WSS M2C961-A1	Meets Requirements
GM 4718M	Meets Requirements
GM 6094M	Meets Requirements
ILSAC GF-4, GF-3, GF-2, GF-1	Meets Requirements
ILSAC GF-5	Meets Requirements
ILSAC GF-6A	Approved